納 入 仕 様 書

DR0727-9001SM-I
DR0727-9001SM-I-4ME
DR0727-9001SM-I-6.5ME
DR0727-9001SM-I-15ME

IDY © 2017-2018 IDY Corporation

改版履歴

版数	日付	承認者	改版者	改版内容
N4.0	2018 年 11 月 12 日	中嶋	正木	Rev3R1 から更新(書式変更) Model DR0727-9001SM-I-4M 追加 iEC1M 仕様書追加
N4.1	2023 年 2 月 15 日	中嶋	正木	型番変更　(旧) DR0727-9001SM-I-4M (新)DR0727-9001SM-I-4ME (旧) DR0727-9001SM-I-14.5M (新)DR0727-9001SM-I-14.5ME (延長ケーブル付きアンテナは型番末尾に E を付加) 「延長ケーブル(iEC1M)仕様」 差替 「延長ケーブル(iEC12M)仕様」 差替 Band B40 データ(2302.5MHz/2350MHz/2397.5MHz)追加
N4.2	2023 年 2 月 28 日	中嶋	正木	“Antenna Orientation Definition(X/Y/Z)” 追加
N4.3	2023 年 2 月 7 日	中嶋	正木	梱包仕様変更 (iEC1M) IDY 住所変更
N4.4	2025 年 7 月 2 日	大野	正木	IDY FAX 番号削除 アンテナ本体 RoHS2 データ追加
N4.5	2026 年 2 月 2 日	大野	正木	① 延長ケーブル3.5m(iEC3.5M)付きモデル DR0727-9001SM-I-6.5ME追加

IDY © 2017-2018 IDY Corporation

■ 適用

本仕様書は、株式会社IDY（以下、「IDY」という）が供給する 3G/LTE/WiMAX および WiMAX2+向け
アンテナ DR0727-9001 シリーズの納入仕様書である。

■ 仕様

1. 型名　DR0727-9001SM-I　：アンテナ本体（ケーブル長 3m）のみ
   DR0727-9001SM-I-4ME　：アンテナ本体（ケーブル長 3m）＋1m 延長ケーブル（iEC1M）
   DR0727-9001SM-I-6.5ME：アンテナ本体（ケーブル長 3m）＋3.5m 延長ケーブル（iEC3.5M）
   DR0727-9001SM-I-15ME：アンテナ本体（ケーブル長 3m）＋12m 延長ケーブル（iEC12M）
2. 用途　3G/LTE/WiMAX および WiMAX2+通信モジュールに接続し使用される。

IDY © 2017-2018 IDY Corporation

3. 電気特性

Frequency	**700 ~ 960 MHz, 1427.9~1462.9 MHz** **1710 ~ 2700 MHz**
V.S.W.R.	**<= 3.0 @ 700 ~ 960 MHz, 1427.9~1462.9 MHz** **<= 2.0 @1710~2700 MHz**
Peak Gain	**0.2 dBi @700 ~ 960 MHz** **2.0 dBi @1710 ~2170 MHz** **3.0 dBi @2300 ~ 2700 MHz** **-6.2 dBi @1427.9~1462.9MHz**
Impedance	**50 Ohm**

4. 使用部材

Material of Radiator	**PCB**
Material of Plastic	**PC+ABS**
Cable Type	**RG174**
Connector Type	**SMA Male**

5. 環境性能

Operation Temperature	**- 40 ˚C ~ + 65 ˚C**
Storage Temperature	**- 40 ˚C ~ + 80 ˚C**

6. シール仕様

IDY 供給品については下記のシール(サイズ:25mm×7mm)をアンテナ本体またはビニール袋に貼付。

LTE 用




WiMAX/WiMAX2+用




IDY © 2017-2018 IDY Corporation


7. パラメータテスト結果



© 2017-2018 IDY Corporation




（追加測定:2023 年 2 月）











© 2017-2018 IDY Corporation

8. 放射特性

810MHz	817.5MHz	822.5MHz
		




824MHz	827.5MHz	832.5MHz
		

837.5MHz	842.5MHz	850MHz
		

IDY © 2017-2018 IDY Corporation




周波数（MHz）	810	817.5	822.5	824	827.5	832.5	837.5	842.5	850
TRP (dBm)	-11.11	-10.82	-10.07	-9.69	-9.46	-9.42	-9.54	-9.6	-9.59
Peak EIRP (dBm)	-4.38	-3.82	-2.97	-2.56	-2.29	-2.37	-2.76	-3.16	-3.77
NHPRP +/- 45 (degree)	-12.45	-12.12	-11.36	-10.98	-10.75	-10.71	-10.82	-10.88	-10.87
NHPRP +/- 30 (degree)	-13.77	-13.47	-12.73	-12.36	-12.14	-12.1	-12.17	-12.2	-12.12
E-Theta Peak Gain (dBi)	-7.55	-6.97	-6.09	-5.67	-5.39	-5.47	-5.88	-6.3	-6.93
E-Phi Peak Gain (dBi)	-6.04	-5.95	-5.39	-5.08	-4.95	-5.05	-5.27	-5.45	-5.72
最大利得（dBi）	-4.38	-3.82	-2.97	-2.56	-2.29	-2.37	-2.76	-3.16	-3.77
指向性（dBi）	6.74	6.99	7.1	7.12	7.16	7.04	6.77	6.44	5.82
放射効率（%）	7.74	8.29	9.85	10.75	11.33	11.43	11.13	10.96	10.98



IDY © 2017-2018 IDY Corporation




902.5MHz	907.5MHz	912.5MHz
		

周波数（MHz）	902	907.5	912.5
TRP (dBm)	-12.02	-11.51	-11.11
Peak EIRP (dBm)	-4.66	-5.11	-5.76
NHPRP +/- 45 (degree)	-13.81	-13.21	-12.72
NHPRP +/- 30 (degree)	-15.29	-14.67	-14.17
E-Theta Peak Gain (dBi)	-9.35	-8.82	-8.23
E-Phi Peak Gain (dBi)	-4.73	-5.16	-5.79
最大利得（dBi）	-4.66	-5.11	-5.76
指向性（dBi）	7.36	6.4	5.35
放射効率（%）	6.28	7.06	7.75

IDY © 2017-2018 IDY Corporation

1430.4MHz	1445.4MHz	1450.4MHz
		




1460.4MHz	1575.42MHz
	




1747.4MHz	1764.9MHz	1782.4MHz
		



© 2017-2018 IDY Corporation

周波数（MHz）	1430.4	1445.4	1450.4	1460.4	1575.42	1747.4	1764.9	1782.4
TRP (dBm)	-13.62	-13.09	-12.89	-12.46	-9.68	-11.52	-11.77	-12.07
Peak EIRP (dBm)	-7.3	-6.82	-6.62	-6.22	-4.45	-7.09	-7.65	-8.34
NHPRP +/- 45 (degree)	-15.06	-14.53	-14.32	-13.86	-10.88	-12.42	-12.7	-12.99
NHPRP +/- 30 (degree)	-16.54	-15.99	-15.81	-15.39	-12.47	-13.62	-13.85	-14.06
E-Theta Peak Gain (dBi)	-11.88	-11	-10.76	-10.28	-6.72	-9.37	-9.6	-9.91
E-Phi Peak Gain (dBi)	-7.41	-6.93	-6.72	-6.3	-4.6	-7.17	-7.72	-8.79
最大利得（dBi）	-7.3	-6.82	-6.62	-6.22	-4.45	-7.09	-7.65	-8.34
指向性（dBi）	6.32	6.27	6.27	6.24	5.23	4.43	4.12	3.73
放射効率（%）	4.34	4.91	5.13	5.67	10.76	7.05	6.66	6.2

IDY © 2017-2018 IDY Corporation

1920MHz	1922.5MHz	1927.5MHz
		

1977.5MHz	2550MHz	2595MHz
		


2640MHz	2650MHz
	

IDY © 2017-2018 IDY Corporation

周波数（MHz）	1920	1922.5	1927.5	1977.5	2550	2595	2640	2650
TRP (dBm)	-13.73	-13.72	-13.7	-13.72	-11.04	-11.2	-11.24	-11.44
Peak EIRP (dBm)	-9.73	-9.72	-9.7	-9.8	-6.99	-6.91	-6.66	-6.79
NHPRP +/- 45 (degree)	-14.65	-14.65	-14.64	-14.72	-11.92	-12.09	-12.2	-12.42
NHPRP +/- 30 (degree)	-16.09	-16.09	-16.08	-16.18	-13.1	-13.25	-13.46	-13.7
E-Theta Peak Gain (dBi)	-10.07	-10.07	-10.07	-10.14	-8.81	-9.28	-9.41	-9.58
E-Phi Peak Gain (dBi)	-10.22	-10.2	-10.16	-10.09	-7.31	-7.82	-7.81	-8
最大利得（dBi）	-9.73	-9.72	-9.7	-9.8	-6.99	-6.91	-6.66	-6.79
指向性（dBi）	4	4	4	3.92	4.04	4.29	4.58	4.64
放射効率（%）	4.24	4.25	4.26	4.25	7.88	7.59	7.51	7.18


IDY © 2017-2018 IDY Corporation

（追加測定:2023 年 2 月）




Frequency (MHz)	Horizontal	Vertical	Total
Tot. Rad. Pwr. (dBi)	-7.61	-14.37	-6.78
Peak EIRP (dBi)	-5.06	-8.47	-3.99
Directivity (dBi)	2.54	5.9	2.79
Efficiency (dB)	-7.61	-14.37	-6.78
Efficiency (%)	17.35	3.66	21.01
Gain (dBi)	-5.06	-8.47	-3.99

IDY © 2017-2018 IDY Corporation




Frequency (MHz)	Horizontal	Vertical	Total
Tot. Rad. Pwr. (dBi)	-7.42	-15	-6.73
Peak EIRP (dBi)	-2.27	-9.14	-2.01
Directivity (dBi)	5.16	5.86	4.72
Efficiency (dB)	-7.42	-15	-6.73
Efficiency (%)	18.09	3.16	21.25
Gain (dBi)	-2.27	-9.14	-2.01

IDY © 2017-2018 IDY Corporation




Frequency (MHz)	Horizontal	Vertical	Total
Tot. Rad. Pwr. (dBi)	-8.03	-13.43	-6.93
Peak EIRP (dBi)	-2.79	-7.07	-2.56
Directivity (dBi)	5.23	6.36	4.37
Efficiency (dB)	-8.03	-13.43	-6.93
Efficiency (%)	15.75	4.54	20.29
Gain (dBi)	-2.79	-7.07	-2.56

IDY © 2017-2018 IDY Corporation




Frequency (MHz)	Horizontal	Vertical	Total
Tot. Rad. Pwr. (dBi)	-8.21	-15.9	-7.52
Peak EIRP (dBi)	-5.45	-10.95	-5.39
Directivity (dBi)	2.76	4.95	2.14
Efficiency (dB)	-8.21	-15.9	-7.52
Efficiency (%)	15.12	2.57	17.69
Gain (dBi)	-5.45	-10.95	-5.39

IDY © 2017-2018 IDY Corporation




Frequency (MHz)	Horizontal	Vertical	Total
Tot. Rad. Pwr. (dBi)	-7.5	-15.99	-6.93
Peak EIRP (dBi)	-3.03	-10.29	-2.79
Directivity (dBi)	4.47	5.69	4.14
Efficiency (dB)	-7.5	-15.99	-6.93
Efficiency (%)	17.77	2.52	20.28
Gain (dBi)	-3.03	-10.29	-2.79

IDY © 2017-2018 IDY Corporation




Frequency (MHz)	Horizontal	Vertical	Total
Tot. Rad. Pwr. (dBi)	-8.49	-15.24	-7.66
Peak EIRP (dBi)	-3.89	-8.46	-3.59
Directivity (dBi)	4.6	6.78	4.07
Efficiency (dB)	-8.49	-15.24	-7.66
Efficiency (%)	14.16	2.99	17.16
Gain (dBi)	-3.89	-8.46	-3.59

IDY © 2017-2018 IDY Corporation




Frequency (MHz)	Horizontal	Vertical	Total
Tot. Rad. Pwr. (dBi)	-6.74	-15.9	-6.24
Peak EIRP (dBi)	-3.71	-10.89	-3.62
Directivity (dBi)	3.03	5	2.63
Efficiency (dB)	-6.74	-15.9	-6.24
Efficiency (%)	21.18	2.57	23.76
Gain (dBi)	-3.71	-10.89	-3.62

IDY © 2017-2018 IDY Corporation



Frequency (MHz)	Horizontal	Vertical	Total
Tot. Rad. Pwr. (dBi)	-7.14	-16.27	-6.64
Peak EIRP (dBi)	-2.25	-10.87	-2.12
Directivity (dBi)	4.89	5.41	4.52
Efficiency (dB)	-7.14	-16.27	-6.64
Efficiency (%)	19.3	2.36	21.66
Gain (dBi)	-2.25	-10.87	-2.12


IDY © 2017-2018 IDY Corporation



Frequency (MHz)	Horizontal	Vertical	Total
Tot. Rad. Pwr. (dBi)	-7.86	-15.46	-7.16
Peak EIRP (dBi)	-4.23	-10.51	-4
Directivity (dBi)	3.62	4.95	3.16
Efficiency (dB)	-7.86	-15.46	-7.16
Efficiency (%)	16.38	2.85	19.23
Gain (dBi)	-4.23	-10.51	-4


IDY © 2017-2018 IDY Corporation

Antenna Orientation Definition（X/Y/Z）



IDY © 2017-2018 IDY Corporation

9. アンテナ外観仕様




No.	Part Number	Name	Material	Finish	Q'ty
7	GS-DR90-01ME	3M Adhesive	G8050F	Red	1
6	COVE-DR90-02B	下盖	PC/ABS	Black	1
5	SCREW-M5020-SUS	Screw	Fe		3
4	COVE-DR90-01B	上盖	PC/ABS	Black	1
3	R-RG-174H	Cable	RG174	Black	1
2	R-HSTUBE-004T	Hot Shrink Tube	EVA	Ø4.0 Black	1
1	SMA010-CGT574-B	SMA Male	Cu	Au Plating	1


© 2017-2018 IDY Corporation

10. 梱包仕様


1. 1PCS装一PE 袋
3PCS螺丝用1小
夹链袋分开包装.




2. 将用夹链袋包装好的螺丝与产品一起放入PE袋




3. 每一格子放入1PCS产品，10PCS放一层





3. 50PCS/每箱



封箱,在側面貼一環保標貼與一外箱標貼.

IDY © 2017-2018 IDY Corporation

11. RoHS2 Data

SGS 台灣網站 → http://twap.sgs.com/sgsrsts/chn/cheres_tw.asp
SGS 大陸網站 → http://rsts.cn.sgs.com/chn/cheres_cn.asp
SGS 韓國網站 → http://rohs.kr.sgs.com/sgsrsts/en/cheres_en.asp

COR/F-G-47a

請輸入以下報告正確資料及檢查碼以便查核
1. 報告編號
2. 報告日期 (YYYY/MM/DD)
3. 產品名稱 (輸入前 10 個字不含空白)
4. 圖示檢查碼 (依指示畫面)

物料中HSF對象物質含量調查表

物料名稱：DR0727-9001SM-I (DR0727-9004BSM)


序號	物料型號	物料各構成名稱	各構成物料的材質	測試報告裡RoHS2.0對應物質測試結果										檢測報告編號	測試日期	測試名稱	測試機構名稱
				Cd	Pb	Hg	Cr(VI)	PBBs	PBDEs	DBP	BBP	DIBP	DEHP				
1	COVE-DR90-03PAB COVE-DR90-04PAB	Cove	PA66+GF15	N.D.	N.D.	N.D.	N.D.	N.D.	N.D.	N.D.	N.D.	N.D.	N.D.	A2250213123101001C	2025.04.09	PA66	SGS
2			黑色色母	N.D.	N.D.	N.D.	N.D.	N.D.	N.D.	N.D.	N.D.	N.D.	N.D.	A2250263976101001E	2025.04.29	彩色母粒	CTI
3	SCREW-T525-IRON	Screw	碳钢	N.D.	N.D.	N.D.	N.D.							SZXEC25000335503	2025.02.20	Carbon spring steel wire	SGS
4			鎳	N.D.	74	N.D.	N.D.							SZXEC25002063405	2025.06.16	Nickel plating	SGS
5	GS-DR90-01ME	3M Adheslve	3M	N.D.	N.D.	N.D.	N.D.	N.D.	N.D.	N.D.	N.D.	N.D.	N.D.	CANEC24019229201	2024.09.04	5423	SGS
6	R-HSTUBE-004W-2	EVA	EVA	N.D.	N.D.	N.D.	N.D.	N.D.	N.D.	N.D.	N.D.	N.D.	N.D.	CANEC24006322203	2025.03.21	HEAT SHRINKABLE	SGS
7	SMA010-CGT574-A	SMA Male	銅	43	28146	N.D.	N.D.	N.D.	N.D.	N.D.	N.D.	N.D.	N.D.	CANPC25009215005	2025.04.30	Brass rod (C3604)	SGS
8			鍍金	N.D.	87	N.D.	N.D.							SZXEC25002063401	2025.06.16	Gold plating	SGS
9	PB-DR90-04FG-Y	PCB	FR4	N.D.	17	N.D.	N.D.	N.D.	N.D.	N.D.	N.D.	N.D.	N.D.	CANEC24019790709	2024.09.14	-4.0 CCL&insulating boa	SGS
10	R-RG-174H-03	Cable	PVC	N.D.	N.D.	N.D.	N.D.	N.D.	N.D.	N.D.	N.D.	N.D.	N.D.	SZXEC25001785002	2025.05.28	PVC 胶粒 红色 白色 黑色	SGS
			PE	N.D.	N.D.	N.D.	N.D.	N.D.	N.D.	N.D.	N.D.	N.D.	N.D.	CANEC24022240617	2024.10.22	PE	SGS
			镀锡铜	N.D.	N.D.	N.D.	N.D.	N.D.	N.D.	N.D.	N.D.	N.D.	N.D.	SZXEC25000424905	2025.02.27	Tinned copper wire	SGS
			镀锡铜	N.D.	N.D.	N.D.	N.D.	N.D.	N.D.	N.D.	N.D.	N.D.	N.D.	SZXEC25000424905	2025.02.27	Tinned copper wire	SGS

根據測試報告如實填寫鉛、鎘、汞、六價鉻、PBBs和PBDEs六項禁用物質的含量
包裝材料中鉛、鎘、汞、六價鉻總含量不超過100ppm，鎘的允許濃度為5ppm
歐盟ROHS指令豁免條款2015/863/EU、钢中合金元素中的铅含量达0.35%、铝含量达0.4%、铜合金中的铅含量达4%

IDY © 2017-2018 IDY Corporation


■ 1m 延長ケーブル iEC1M 仕様


＜iEC1M Mechanical Drawings＞




© 2017-2018 IDY Corporation


＜iEC1M Test Data＞










IDY © 2017-2018 IDY Corporation







IDY © 2017-2018 IDY Corporation



© 2017-2018 IDY Corporation


＜iEC1M Packaging Specification＞

Product packaging specification


Date：2023.07.07 page: 1 of 1

P/N : SMAMN8-1L1M-SMASFN8 Model : iEC1M	Edition ：D
Product Name :Coaxial Cable	Customer : ALL

一




二



5PCS / BAG


三

SIDE



Put a ROHS label on the side of master carton,
fill in the product part number, quantity, net weight and gross weight.


四



五

FRONT





500PCS / CARTON

APPROVED BY : _____ CHECKED BY : _____ DESIDNED BY ： _____

© 2017-2018 IDY Corporation

＜iEC1M Cable Specification＞


穗格 WWW. SUI RONGCABLE. COM 深圳市穗榕同轴电缆科技有限公司

S.R Code:SR18070201

LMR-100 Coaxial Cable Specification

（**LMR-100** 同轴电缆规格书）

Reference standard:MIL-C-17G Black

Type of coaxial cable: LMR-100, RoHS compliance					
Legend:					
LMR-100 1.Inner conductor 内导体 2. Dielectric: 绝 缘 3.Outer conductor 外导体 4. Jacket White 护套					
Main Electrical properties:					
Characteristic impedance	阻抗	50±2Ohm			
Rated capacitance	电容	100±2 pf/m			
Velocity	速比	66%			
Delay	延时	4.90ns/m			
Operating frequency	工作频率	1~6000MHz			
Attenuation at typical frequencies:（dB/ m）					
100MHz	400MHz	900MHz	1800MHz	2400MHz	3000MHz
0.19	0.48	0.74	1.08	1.25	1.48
VSWR 1~3000MHz	电压驻波比	1.30 Max.			
Mechanical Construction:					
Inner conductor: BC	裸铜线	0.46±0. 01mm			
Dielectric:PE	绝缘 PE	1.52±0. 03mm			
Outer conductor: AP+TC（※）	铝箔+镀锡铜线	2.04±0. 05mm （16*5/0.10mm）			
Jacket :PVC	护套阻燃黑色 PVC （防火等级：VW-1）	2.80±0.10mm			
※ TC-- tinned copper					
Engineering data:					
Maximum Pull Tension Minimum bending radius Operating temperature Reel Length jacket-Marking	最大拉拔力 最小弯曲半径 工作温度 装盘长度 产品标识	38 lbs 27mm -40~+105°C LOW LOSS 100 VW-1 PVC COAXIAL CABLE HYT MICROWAVE SYSTEM/NFC			

SuiRong COAXIAL CABLE Co.,Ltd

制造商:深圳市穗榕同轴电缆科技有限公司
生产地:深圳市龙岗区务地铺清水路清水巷

WWW.SUIRONGCABLE.COM
Tel：+86-755-28217358 Fax+86-755-28217359
2018-07-02

IDY © 2017-2018 IDY Corporation

＜iEC1M RoHS Test＞

SGS TaiBei Network---http://twap.sgs.com/sgsrsts/chn/cheres_tw.asp

SGS Mainland Network---http://rsts.cn.sgs.com/zh-cn/cheres_cn.asp

SGS Korea S. Network---http://rohs.kr.sgs.com/sgsrsts/en/cheres_en.asp

PLS fill out the correct data for search

1.Report Number

2.Report Date(YYYY/MM/DD)
3.Product Name(Input the first 10 figures. Do not include the blank)
4.The graphic presentation checking yard

HSF Datasheet

Part Number：SMAMN8-1L1M-SMASFN8 IDY P/N: iEC1M

Number	Detali Part Number	Detail Name	Material	RoHS Test Results										Report Number	Test Date	Test Name	Test Locale
				Cd	Pb	Hg	Cr(VI)	PBBs	PBDEs	DBP	BBP	DIBP	DEHP				
1	SMA	180°Male 180°Female	CU	N.D.	29790	N.D.	Negative	N.D.	N.D.	N.D.	N.D.	N.D.	N.D.	AZT032106150008C-011	2021.07.05	C3604	AZT
			Au Plated	N.D.	31	N.D.	N.D.							SZXEC2101871802	2021.06.28	銅車件電鍍金.	SGS
			PTFE	N.D.	N.D.	N.D.	N.D.	N.D.	N.D.	N.D.	N.D.	N.D.	N.D.	A2200357261101001	2020.10.17	PTFE plastics	CTI
2	LMR100	Cable	PVC	N.D.	N.D.	N.D.	N.D.	N.D.	N.D.	N.D.	N.D.	N.D.	N.D.	CANEC2020811102	2020.11.27	PVC Black	SGS
			PE	N.D.	N.D.	N.D.	N.D.	N.D.	N.D.	N.D.	N.D.	N.D.	N.D.	CANEC2022021108	2020.12.18	HDPE	SGS
			AL	N.D.	N.D.	N.D.	N.D.	N.D.	N.D.	N.D.	N.D.	N.D.	N.D.	YCCT332020060601RZ2	2020.06.06	铝箔聚酯膜麦拉带	YCCT
			BCU	N.D.	N.D.	N.D.	N.D.	N.D.	N.D.	N.D.	N.D.	N.D.	N.D.	TSNEC2002256101	2020.11.30	ELECTRICIAN	SGS
			TCU	N.D.	N.D.	N.D.	N.D.	N.D.	N.D.	N.D.	N.D.	N.D.	N.D.	C210301069002-0	2021.03.05	镀锡线0.15	CPST
3	HSTUBE-035N-WP	Shrink Tub	EVA	N.D.	N.D.	N.D.	N.D.	N.D.	N.D.	N.D.	N.D.	N.D.	N.D.	CANEC2022443601	2020.12.22	HEAT SHRINKABLE TUBING	SGS

PLS refer the SGS report, fill out the content of Pb, Cd, Hg, Cr6+, PBBs, PBDEs
The content of Pb, Cd, Hg, Cr6+, PBBs, PBDEs is less than 100 ppm in the package. The content of Cd is less than 5 ppm.
According to the EU ROHS directive exemption clause 2015/863/EU Lead as an alloying element in steel containing up to 0,35 % aluminium containing up to 0,4% copper alloy containing up to 4%

IDY © 2017-2018 IDY Corporation

■ 3.5m 延長ケーブル iEC3.5M 仕様

納入仕様書

Model：iEC3.5M

3.5m Extension Cable

IDY © 2017-2018 IDY Corporation

Index:

1. Revision History / Page 3

2. Specification / Page 4

3. Characteristics and Reliability Test / Page 5

4. S Parameter Test Data / Page 6

5. Mechanical and Packing Drawing / Page 7 ~ 8

6. Material Description and RoHS Test Report / Page 9 ~ end

IDY © 2017-2018 IDY Corporation

1. Revision History

Revision	Date	Change Notification	Description
1.0	2025.09.29	First Edition	

IDY © 2017-2018 IDY Corporation

2. Specification

Sample Photo	
	
A. Electrical Characteristics	
Frequency	DC~ 6 GHz
Impedance	50 Ohm
V.S.W.R.	<= 1.8
Insertion Loss	4.5 dB
Voltage (breakdown)	> 500V
Insulation Resistance	>= 500 M ohm
B. Mechanical Characteristics	
Pull Test of Connector	>= 3 Kg
Mating Cycles	> 500
C. Environmental	
Operation Temperature	- 40 ˚C ~ + 75 ˚C
Storage Temperature	- 40 ˚C ~ + 80 ˚C


IDY © 2017-2018 IDY Corporation

3. Characteristics and Reliability Test

Test Items 測試項目		Test Condition and Procedure 測試方法	Requirements 要求	Result 結果
C1	V.S.W.R. 電壓駐波比	Set DUT on Network Analyzer; make individual calibration to test 設置網路分析儀參數進行測試	Directive DUT specification 符合待測物規範	PASS
C2	Insertion Loss 插入損失	Set DUT on Network Analyzer; make individual calibration to test 設置網路分析儀參數進行測試	Directive DUT specification 符合待測物規範	PASS
M4	Pull Test 拉力	Holding with individual specification; force applied to axis of terminal .單獨定義產品端子拉力	1. Directive DUT specification 2. Frequency Tol.≤5% 符合待測物規範;頻率偏移≤5%	PASS
M6	Dimension 尺寸	Inspection of dimension, color, material, package, surface process.檢查尺寸,顏色,材料,包裝,表面處理	Directive DUT specification 符合待測物規範	PASS
E2	Salt Spray 鹽霧	GB / T 2423.17-2008 Temp: 35°C; RH: ≥ 95%; NaCl solution: ≥ 5%;Time: 24H 溫度 35°C;濕度≥95%;鹽水濃度≥5%;測試 24H	1. No Visual Damage 2. Frequency Tol.≤5% 無明顯外觀不良;頻率偏移≤5%	PASS
E3	Temperature and Humidity Chamber 恒溫恒濕	GB / T 2423.3-2006 Temp: 80°C / 12 H; -40°C / 12H RH: ≥ 90%; Time: 24H 溫度 80°C 測試 12H 轉-40°C 測試 12H;濕度≥ 90%;時間 24H	After 2 Hours Recovery 1. No Visual Damage 2. Frequency Tol.≤5% 恢復 2H 後, 無明顯外觀不良;頻率偏移≤5%	PASS
E5	Aging test 老化	GB /T 2423.2 - 2008 Temp: 80°C; Time: 24 hours 溫度 80° C, 測試 24H	After 2 Hours Recovery 1. No Visual Damage 2. Frequency Tol.≤5% 無明顯外觀不良;頻率偏移≤5%	PASS
R1	RoHS	With Reference to IEC 62321:2008 with flow chart 參考 IEC 62321 測試流程	Directive RoHS 2011/65/EU 符合 RoHS 2011/65/EU 標準	PASS
R2	PFOS	With Reference to USA EPA 3550C:1996 by LC/MS 參考 USA EPA 3550C 測試流程	Directive RoHS 2006/122/EC 符合 RoHS 2011/65/EU 標準	PASS


IDY © 2017-2018 IDY Corporation

4. S Parameter Test Data



IDY © 2017-2018 IDY Corporation

5. Mechanical and Packing Drawing




© 2017-2018 IDY Corporation

PACKING CRITERION


Date:2025.09.10

Part Number : iEC3.5M	Revision :A
Name: Cable	

一




二




1PCS/per Bag


三




四



五





70pcs per Carton

IDY © 2017-2018 IDY Corporation


6. Material Description and RoHS Test Report

穗格 WWW.SUIRONGCABLE.COM 深圳市穗榕同轴电缆科技有限公司

S.R Code: 19082702

LMR-200 Coaxial Cable Specification

（ LMR-200 同轴电缆规格书）

Type of coaxial cable: LMR-200					
Legend:					
LMR-200: 1.Inner conductor 内导体 2. Insulation 电缆芯线 3.Outer conductor 外导体 4. Jacket 护套					
Main Electrical properties:					
Characteristic impedance	阻抗	50±2Ohm			
Rated capacitance	电容	78±2 pf/m			
Velocity	速比	81%			
Operating frequency	工作频率	10~3000MHz			
Attenuation at typical frequencies:（dB/m）					
400MHz	900 MHz	1500 MHz	2100MHz	3000MHz	6000MHz
0.220	0.341	0.450	0.551	0.639	1.32
VSWR 10~3000MHz	电压驻波比	1.30Max.			
Mechanical Construction:					
Inner conductor: BC	裸铜线	1.12±0.005mm			
Dielectric:foam PE	绝缘 LLDPE	2.95±0.10mm			
Outer conductor: APA+TC	铝塑覆合箔＋镀锡铜线	3.70±0.12mm（16*6/0.12mm）			
Jacket : PVC Black	护套黑色 PVC	5.0±0.10mm			
Engineering data:					
Maximum Pull Tension	最大拉拔力	42 Ibs			
Minimum bending radius	最小弯曲半径	50mm			
Operating temperature	工作温度	-25~+80°C			
Reel Length	装盘长度	/			
jacket-Marking	产品标识	LOW LOSS 200 PVC COAXIAL CABLE HYT MICROWAVE SYSTEM/NFC			

SuiRong COAXIAL CABLE Co.,Ltd

制造商:深圳市穗榕同轴电缆科技有限公司
生产地:深圳市龙岗区龙西务地铺清水路清水巷 40 号

WWW.SUIRONGCABLE.COM
Tel：+86-755-28217358 Fax+86-755-28217359

2019-08-27

Page 9

SGS 台灣網站 → http://twap.sgs.com/sgsrsts/chn/cheres_tw.asp
SGS 大陸網站 → http://rsts.cn.sgs.com/chn/cheres_cn.asp
SGS 韓國網站 → http://rohs.kr.sgs.com/sgsrsts/en/cheres_en.asp

請輸入以下報告正確資料及檢查碼以便查核
1. 報告編號
2. 報告日期 (YYYY/MM/DD)
3. 產品名稱 (輸入前 10 個字不含空白)
4. 圖示檢查碼 (依指示畫面)

物料中HSF對象物質含量調查表

物料名稱：SMAMN8-2L3M5-SMASFN8 (iEC3.5M)

序號	物料型號	物料各構成名稱	各構成物料的材質	測試報告裡RoHS對應物質測試結果										檢測報告編號	測試日期	測試名稱	測試機構名稱
				Cd	Pb	Hg	Cr(VI)	PBBs	PBDEs	DBP	BBP	DIBP	DEHP				
1	SMA	SMA Male SMA Female	銅	43	28146	N.D.	N.D.	N.D.	N.D.	N.D.	N.D.	N.D.	N.D.	CANPC25009215005	2025.04.30	Brass rod (C3604)	SGS
2			鍍金	N.D.	87	N.D.	N.D.							SZXEC25002063401	2025.06.16	Gold plating	SGS
3		Insulator	PTFE	N.D.	N.D.	N.D.	N.D.	N.D.	N.D.	N.D.	N.D.	N.D.	N.D.	TAOPC24009783803	2024.12.13	TFE MOLDING POWDEF	SGS
4	HSTUBE	HSTUBE	EVA	N.D.	N.D.	N.D.	N.D.	N.D.	N.D.	N.D.	N.D.	N.D.	N.D.	CANEC25012572003	2025.06.05	HEAT SHRINKABLE TUBING	SGS
5	LMR200	Cable	PVC	N.D.	N.D.	N.D.	N.D.	N.D.	N.D.	N.D.	N.D.	N.D.	N.D.	SZXEC25001785002	2025.05.28	PVC 胶粒 红色 白色 黑色	SGS
6			PE	N.D.	N.D.	N.D.	N.D.	N.D.	N.D.	N.D.	N.D.	N.D.	N.D.	CANEC24022240617	2024.10.22	PE	SGS
7			裸铜	N.D.	N.D.	N.D.	N.D.	N.D.	N.D.	N.D.	N.D.	N.D.	N.D.	SZXEC25000424913	2025.02.27	Copper wire	SGS
8			镀锡铜	N.D.	N.D.	N.D.	N.D.	N.D.	N.D.	N.D.	N.D.	N.D.	N.D.	SZXEC25000424905	2025.02.27	Tinned copper wire	SGS
9			AL	N.D.	N.D.	N.D.	N.D.	N.D.	N.D.	N.D.	N.D.	N.D.	N.D.	NGBEC25000789619	2025.02.21	aluminium polyester foil	SGS

根據測試報告如實填寫鉛、鎘、汞、六價鉻、PBBs和PBDEs六項禁用物質的含量
包裝材料中鉛、鎘、汞、六價鉻總含量不超過100ppm，鎘的允許濃度為5ppm
歐盟ROHS指令豁免條款2015/863/EU，鋼中合金元素中的鉛含量達0.35%、鋁含量達0.4%、銅合金中的鉛含量達4%

IDY © 2017-2018 IDY Corporation

■ 12m 延長ケーブル iEC12M 仕様

Product Number: iEC12M
Product Name: Coaxial Cable

Specification For Approval

Date: 2021 / 09 / 13

File No.: 210802001

Version: 1.2

IDY P/N : iEC12M

R/N : SMAMN8-2L12M-SMASFN8

Description : Coaxial Cable

Checked By:
Approved By:

Page 1

IDY © 2017-2018 IDY Corporation

Product Number: iEC12M
Product Name: Coaxial Cable

Index:

1. **Revision History / Page 3**
2. **Specification / Page 4**
3. **Characteristics and Reliability Test / Page 5**
4. **S Parameter Test Data / Page 6 ~ 13**
5. **Mechanical and Packing Drawing / Page 14 ~ 15**
6. **Material Description and RoHS Test Report / Page 16 ~ end**

IDY © 2017-2018 IDY Corporation

Product Number: iEC12M
Product Name: Coaxial Cable

1. Revision History

Revision	Date	Change Notification	Description
1.0	2020.09.25	Issued	
1.1	2021.08.02	Added Data	Increased the measurement frequency.
1.2	2021.09.13	Changed Packaging Specifications	The packaging specifications have been changed to the English version.

IDY © 2017-2018 IDY Corporation

Product Number: iEC12M
Product Name: Coaxial Cable

2. Specification

Sample Photo	
	
A. Electrical Characteristics	
Frequency	701~713MHz / 745~826 MHz 832~847MHz / 876~897MHz 867~1712MHz / 1852~1900MHz 1445~1977MHz / 1842~2687MHz 1782~2647MHz / 2400~5470MHz 3302~4197 MHz / 4402~4997 MHz 5597~5725 MHz / 1575~1561MHz
Impedance	50 Ohm
Insertion Loss	>= -4.0 dB @ 701~713MHz >= -4.0 dB @745~826 MHz >= -4.2 dB @832~847MHz >= -4.2 dB @876~897MHz >= -4.2 dB @867~952 MHz >= -5.6 dB @1430~1712MHz >= -5.5 dB @1575~1561MHz >= -6.3 dB @1852~1900MHz >= -6.3 dB @1445~1977MHz >= -8.0 dB @1842~2687MHz >= -7.0 dB @1782~2647MHz >= -12 dB @2400~5470MHz >= -10 dB @3302~4197 MHz >= -12 dB @4402~4997 MHz >= -12 dB @5597~5725 MHz
Voltage (breakdown)	> 500V
Insulation Resistance	>= 500 M ohm
B. Mechanical Characteristics	
Pull Test of Connector	>= 5Kg
Mating Cycles	> 500

IDY © 2017-2018 IDY Corporation

Product Number: iEC12M
Product Name: Coaxial Cable

C. Environmental	
Operation Temperature	- 25 ˚C ~ + 70 ˚C
Storage Temperature	- 30 ˚C ~ + 80 ˚C

3. Characteristics and Reliability Test


Test Items		Test Condition and Procedure	Requirements	Result
C1	V.S.W.R.	Set DUT on Network Analyzer; make individual calibration to test	Directive DUT specification	PASS
C2	Insertion Loss	Set DUT on Network Analyzer; make individual calibration to test	Directive DUT specification	PASS
M4	Pull Test	Holding with individual specification; force applied to axis of terminal.	1. Directive DUT specification 2. Frequency Tol.≤5%	PASS
M6	Dimension	Inspection of dimension, color, material, package, surface process.	Directive DUT specification	PASS
E2	Salt Spray	GB / T 2423.17-2008 Temp: 35°C; RH: ≥ 95%; NaCl solution: ≥ 5%;Time: 24H	1. No Visual Damage 2. Frequency Tol.≤5%	PASS
E3	Temperature and Humidity Chamber	GB / T 2423.3-2006 Temp: 80°C / 12 H; -40°C / 12H RH: ≥ 90%; Time: 24H	After 2 Hours Recovery 1. No Visual Damage 2. Frequency Tol.≤5%	PASS
E5	Aging test	GB /T 2423.2 - 2008 Temp: 80°C; Time: 24 hours	After 2 Hours Recovery 1. No Visual Damage 2. Frequency Tol.≤5%	PASS
R1	RoHS	With Reference to IEC 62321:2008 with flow chart	Directive RoHS 2015/863/EU	PASS

IDY © 2017-2018 IDY Corporation

Product Number: iEC12M
Product Name: Coaxial Cable

4. S Parameter Test Data


701~713MHz




© 2017-2018 IDY Corporation

Product Number: iEC12M
Product Name: Coaxial Cable

745~826MHz




832~847MHz




IDY © 2017-2018 IDY Corporation

Product Number: iEC12M
Product Name: Coaxial Cable

876~897MHz




867~1712MHz




IDY © 2017-2018 IDY Corporation

Product Number: iEC12M
Product Name: Coaxial Cable

1575~1561MHz




1852~1900MHz




IDY © 2017-2018 IDY Corporation

Product Number: iEC12M
Product Name: Coaxial Cable

1445~1977MHz




1842~2687MHz




IDY © 2017-2018 IDY Corporation

Product Number: iEC12M
Product Name: Coaxial Cable

1782~2647MHz




2400~5470MHz




IDY © 2017-2018 IDY Corporation

Product Number: iEC12M
Product Name: Coaxial Cable

3302~4197 MHz




4402~4997 MHz



IDY © 2017-2018 IDY Corporation


Product Number: iEC12M
Product Name: Coaxial Cable

5597~5725MHz



© 2017-2018 IDY Corporation

＜iEC12M Mechanical Drawings＞



NO	Description	Material	Specification	Q'ty
4	SMA	Cu Au plated	180°Female	1
3	Shrink Tube	EVA;Black(No red phosphorus)	Φ6.0*20mm	2
2	Cable	LMR200 ; Balck	L =12000mm	1
1	SMA	Cu Au plated	180°Male	1

IDY Corporation

TITLE: SMA/ LMR200 /SMA

PART NO.:SMAMN8-2L12M-SMASFN8 IDY P/N: iEC12M

APP BY	CHK BY	RF BY	DES BY	UNITS: mm	Tolerance
				SCALE: 1/1	X.X ±0.5
				REVISION: A	X.XX ±0.2
					X° ±1°

IDY © 2017-2018 IDY Corporation


＜iEC12M Packaging Specification＞

Product packaging specification


Date：2021.08.05 IDY P/N: iEC12M page: 1 of 1

Product NO : SMAMN8-2L12M-SMASFN8	Edition：A
Product Name :Coaxial Cable	Customer： ALL

1.




2.




1 PCS / BAG

3.





4.



Put a ROHS label on the side of master carton,
fill in the product part number, quantity, net weight and gross weight.

5.





25PCS / CARTON

APPROVED BY : _____ CHECKED BY : _____ DESIDNED BY：_____

© 2017-2018 IDY Corporation


＜iEC12M Cable Specification＞

穗榕 WWW.SUIRONGCABLE.COM 深圳市穗榕同轴电缆科技有限公司

S.R Code: 18040705

R-CB-LMR-200 Coaxial Cable Specification

（ **LMR-200** 同轴电缆规格书）

Type of coaxial cable: LMR-200				
Legend:				
LMR-200: 1.Inner conductor 内导体 2. Insulation 电缆芯线 3.Outer conductor 外导体 4. Jacket 护套				
Main Electrical properties:				
Characteristic impedance	阻抗	50±2Ohm		
Rated capacitance	电容	78±2 pf/m		
Velocity	速比	81%		
Operating frequency	工作频率	10~3000MHz		
Attenuation at typical frequencies:（dB/m） Remarks: We confirmed that typical frequencies can be up to 6000MHz				
400MHz	900 MHz	1500 MHz	2100MHz	3000MHz
0.220	0.341	0.450	0.551	0.639
VSWR 10~3000MHz	电压驻波比	1.30Max.		
Mechanical Construction:				
Inner conductor: BC	裸铜线	1.12±0. 005mm		
Dielectric:foam PE	绝缘 FPE	2.95±0. 10mm		
Outer conductor: APA+TC	铝塑覆合箔＋镀锡铜线	3.70±0. 12mm（16*6/0.12mm）		
Jacket : PVC Black	护套黑色 PVC	5.0±0.10mm		
Engineering data:				
Maximum Pull Tension	最大拉拔力	42 Ibs		
Minimum bending radius	最小弯曲半径	50mm		
Operating temperature	工作温度	-25~+70°C		
Reel Length	装盘长度	/		
jacket-Marking	产品标识	LOW LOSS 200 PVC HYT CABLE MICROWAVE SYSTEM/NFC		

SuiRong COAXIAL CABLE Co.,Ltd

制造商:深圳市穗榕同轴电缆科技有限公司
生产地:深圳市龙岗区龙西务地铺清水路清水巷 40 号

WWW.SUIRONGCABLE.COM
Tel：+86-755-28217358 Fax+86-755-28217359

2018-04-07

Page 16

＜iEC12M RoHS Test＞

SGS 台灣網站 → http://twap.sgs.com/sgsrsts/chn/cheres_tw.asp
SGS 大陸網站 → http://rsts.cn.sgs.com/chn/cheres_cn.asp
SGS 韓國網站 → http://rohs.kr.sgs.com/sgsrsts/en/cheres_en.asp

請輸入以下報告正確資料及檢查碼以便查核
1. 報告編號
2. 報告日期 (YYYY/MM/DD)
3. 產品名稱 (輸入前 10 個字不含空白)
4. 圖示檢查碼 (依指示畫面)

填表：	
部門：	
職務：	

物料中HSF對象物質含量調查表

物料名稱：SMAMN8-2L12M-SMASFN8 (iEC12M)

序號	物料型號	物料各構成名稱	各構成物料的材質	測試報告裡RoHS2.0對應物質測試結果										檢測報告編號	測試日期	測試名稱	測試機構名稱
				Cd	Pb	Hg	Cr(VI)	PBBs	PBDEs	DBP	BBP	DIBP	DEHP				
1	SMA	180° Female 180°Male	銅	39	32915	N.D.	N.D.							CANML2109847002	2021.06.11	黄銅棒（C3604）	SGS
			鍍金	N.D.	31	N.D.	N.D.							SZXEC2101871802	2021.06.28	銅車件電鍍金.	SGS
2	LMR200	Cable	PVC	N.D.	N.D.	N.D.	N.D.	N.D.	N.D.	N.D.	N.D.	N.D.	N.D.	CANEC2020811102	2020.11.27	PVC Black	SGS
			PE	N.D.	N.D.	N.D.	N.D.	N.D.	N.D.	N.D.	N.D.	N.D.	N.D.	CANEC2022021108	2020.12.18	HDPE	SGS
			AL	N.D.	N.D.	N.D.	N.D.	N.D.	N.D.	N.D.	N.D.	N.D.	N.D.	YCCT332020060601RZ2	2020.06.06	铝箔聚酯膜麦拉带	YCCT
			裸铜	N.D.	N.D.	N.D.	N.D.	N.D.	N.D.	N.D.	N.D.	N.D.	N.D.	TSNEC2002256101	2020.11.30	ELECTRICIAN	SGS
			镀锡铜	N.D.	N.D.	N.D.	N.D.	N.D.	N.D.	N.D.	N.D.	N.D.	N.D.	C210301069002-0	2021.03.05	镀锡线0.15	CPST
3	Shrink Tub	EVA	EVA	N.D.	N.D.	N.D.	N.D.	N.D.	N.D.	N.D.	N.D.	N.D.	N.D.	CANEC2022443601	2020.12.22	HEAT SHRINKABLE TUBING	SGS

根據測試報告如實填寫鉛、鎘、汞、六價鉻、PBBs和PBDEs六項禁用物質的含量
包裝材料中鉛、鎘、汞、六價鉻總含量不超過100ppm，鎘的允許濃度為5ppm
歐盟ROHS指令豁免條款2015/863/EU、鋼中合金元素中的鉛含量达0.35%、铝含量达0.4%、铜合金中的铅含量达4%

IDY © 2017-2018 IDY Corporation

○ お問い合わせ

株式会社IDY
〒101－0032
東京都千代田区岩本町3－9－3　フォレスト秋葉原ビル6階
TEL：03－4400－7970

© 2017-2018 IDY Corporation